



Main

Range	Acti 9
Product name	Acti 9 IHP
Device short name	IHP
Product or component type	Programmable digital time switch
Device application	Building
Battery type	Lithium
Number of channels	1
Provided equipment	Memory key Programming kit
Language	English French German Italian Portuguese Spanish
Colour tint	White (RAL 9003)

Complementary

Power consumption	0.4 W
Maximum switching current	16 A - 250 V AC pf = 1 4 A - 250 V AC pf = 0.6
[Ue] rated operational voltage	230 V[Sapce](- 15...10 %) AC 50/60 Hz
Cycle duration	24 hours + 7 days
Maximum number of switchings	56
Minimum interval duration	1 min
Accuracy	+/- 0.5 s/day 25 °C
Display type	LCD
Battery life	10 yr
Backup time	10 years time and program saving
Mounting support	DIN rail
9 mm pitches	2
Function available	Operating hours counter Automatic winter/summer time changeover
Type of setting	Absence for holidays function PIN code
Connections - terminals	Screwless terminals : 2 x 0.5...2.5 mm ²
Width	18 mm
Height	90 mm
Depth	66 mm
Product weight	0.09 kg

Environment

IP degree of protection	IP20 B
ambient air temperature for operation	-25...55 °C

Offer Sustainability

Sustainable offer status	Green Premium product
--------------------------	-----------------------

RoHS (date code: YYWW)	Compliant - since 1504 - Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Available