

SRK25ZSA-W / DXK09ZSA-W, 2.5KW



KEY FEATURES

- Stylish and Modern Design
- 3D Auto airflow for effective and even air distribution
- Allergen clear system to capture allergens and neutralise bacteria
- R32 refrigerant for higher energy efficiencies
- Optional Wi-Fi control

Indoor			SRK25ZSA-W
Outdoor			SRC25ZSA-W
Power supply			1 Phase 220~240V 50Hz
Capacity	Cooling T1	kW	2.5 (0.9~3.5)
	Heating H1		3.2 (0.9~5.2)
Input	Cooling T1	kW	0.51 (0.18~0.88)
	Heating H1		0.65 (0.21~1.43)
Max running current		A	9
Energy label	Cooling T1	Stars	5
	Heating H1		5
EER	Cooling T1		4.90
COP	Heating H1		4.92
Sound power level (JIS C9612)	Cooling(Outdoor)	dB(A)	58
	Heating(Outdoor)		61
Sound pressure level (JIS C9612)	Cooling(Indoor)	dB(A)	40-31-22-19
	Heating(Indoor)		46-38-24-19
Silent mode sound pressure level	Cooling(Outdoor)	dB(A)	42
	Heating(Outdoor)		43
Airflow	Cooling(Indoor)	l/s	182-140-88-78
	Heating(Indoor)		237-182-110-88
External dimensions (HxWxD)	Indoor	mm	290x870x230
	Outdoor		540x780(+62)x290
Net weight	Indoor	kg	10
	Outdoor		36
Refrigerant piping	Liquid line	mm	Ø6.35
	Gas line		Ø9.52
	Connection method		Flare connection
Refrigerant R32	Quantity	kg	0.75
	Pre charged to pipe length	m	15
Clean filter			Allergen Clear & Photocatalytic Washable Deodorizing Filter