



CLEVERTRONICS I x 36W DIFFUSED BATTEN WITH LED EMERGENCY



PRODUCT INFORMATION

| | |
|-----------------------|---|
| Catalogue Number | LBS236S-DIF-A2 |
| Description | 2 x 36 Watt Diffused Batten with LED Emergency |
| Construction | Powder Coated Steel body with Polycarbonate lamp holders. |
| Mounting | Surface Mount |
| Dimensions L x W x H | 1266mm x 115mm x 108mm |
| Operating Mode | Sustained |
| Testing System | Manual Test Switch |
| Charging Method | Intelligent current limited constant voltage charger |
| Diffuser | Prismatic |
| Ballast | Electronic , 2x36W, EEI=A2 |
| Lamp(s) | T8 Cool White Tri-Phosphorous 36W/840 |
| Emergency Lamp Source | 2 x 3W LED (Lifetime warranty on the lamp head and loom assembly) No dome cover required |
| Operating Voltage | 240V |
| Power Consumption | 72.4 Watts (lamps ON) .4 Watts (lamps OFF) |
| IP Rating | IP20 |
| Operating Temperature | 10° to 40°C |
| AS2293 Classification | C0=D63 C90=C63 |

REPLACEMENT PARTS

| PART NUMBER | DESCRIPTION |
|-------------|--|
| 1310224 | Ballast, Philips HF-P, 2 x 36W, EEI=A2 |
| 3100380 | Lamp(s) 36W/840 T8 Cool White |
| 1120320 | Lamp Holder T8 with Cover |
| 2300110 | Diffuser 28/36W Wide |
| 2900012 | End Caps |
| 3760210 | Emergency End Cap control |