

CLEVERTRONICS L10 OPTIMUM CLEVERFIT PRO LED THEATRE EXIT



PRODUCT INFORMATION

Catalogue Number	LCFPRO-TH-R
Description	LED L10 OPTIMUM Cleverfit Pro Theatre Exit, 24 metre viewing Distance
Construction	Fire-retardant PC/ABS body with Polycarbonate Diffusers
Mounting	Wall, Ceiling Single-Sided & Ceiling Double-Sided
Dimensions L x W x H	367mm x 72mm x 214mm
Operating Mode	Maintained
Testing System	Manual Test Switch
Charging Method	Intelligent current limited constant voltage charger
Diffuser	Theatre Mask (must specify diffuser combination)
Lamp(s)	2 x 1W LED, 100,000 hours
Operating Voltage	240V 50Hz
Power Consumption	3.6W Standby (5.6W during first 16hr charge)
IP Rating	IP20
Operating Temperature	1° to 40°C
AS/NZS2293 Classification	NA – Theatre Mask

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530030	Battery: 3.3 Volt 2.5Ah Li-ion
8002310	PCA: CPROL10 Drvr.ZWC.No Sw.A, #CT10174-L2
8002250	PCA: CPRO LED Board w Loom, #CT10172-A1

