


## CLEVERTRONICS LP PREMIUM LIFELIGHT PRO IP66/67 SURFACE MOUNT EMERGENCY LUMINAIRE



L = 380mm, D = 130mm, H = 190mm

### PRODUCT INFORMATION

Catalogue Number	CWPLIFE-PRO-ZW
Description	Lifelight PRO, High Performance, Surface Mount Emergency Luminaire with Lithium Battery Technology – IP66/67
Mounting	Surface Mount IP66/67 with integral lamp head, charger pack & battery
Dimensions L x W x H	380mm x 130mm x 190mm
Ceiling hole cut-out	N/A
Minimum ceiling depth	N/A
Operating Mode	Non-Maintained
Testing System	Zoneworks Computerised Testing
Charging Method	Intelligent current limited constant voltage charger
Lamps(s)	2 x 3W LED (Lifetime warranty on the lamp head and loom assembly)
Operating Voltage	240V 50Hz
Power Consumption	0.4W (standby) 2.2W (max during 16 hour charge)
IP Rating	IP66/67
Impact Rating	IK08 (side surface) IK09 (front surface)
Operating Temperature	1° to 40°C (Ambient for battery and control gear)
AS/NZ2293 Classification	C <sub>0</sub> =D32 C <sub>90</sub> =D32

### REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1100830	2 x 3W LED Round Head Assembly - White
1550230	Battery: LP 3.2V 6400mAh.200mm lead. Brkt
CWPLIFE-PRO-CKIT-ZW-NP	PCA: Lifelight Pro Control Gear
8001450	PCA: Zoneworks Powerline Node, #CT10310-A6

