

Stanilite Exits

Excel LED Economy Exit



- Features**
- Architecturally pleasing design
 - Unique slide connect bracket that provides strength and enables quick and easy maintenance
 - LED technology 50,000 hours lamp life
 - Emergency classification
 - Includes all pictograph diffuser options
 - High temperature NiCad batteries
 - Universal wall/ceiling mounting, can also be rod or wire suspended
 - Large terminal (16mm²) block for easy wiring

Catalogue No.
EELED

Excel LED Economy Exit

Description	Dimensions	Photometrics	Spare Parts and Accessories
LED Economy Pictograph	Length: 362mm Width: 100mm Height: 224mm (Including Bracket)	C0: D2.5 C90: E2.5 (Preliminary Results)	03-01219: Battery 3 Cell Sub-C NiCad Straight 3.6V 1.6Ah

Economy Exit LED - Maintained Body



- Features**
- LED technology 50,000 hours lamp life
 - Strong, lightweight, UV/FR polycarbonate body and gear tray
 - Wall or ceiling mounting
 - Switched active input available for mains switching
 - Large terminal block (16mm²) for easy wiring
 - Designed for direct replacement of installed 10W Economy Exit EE110M and EE210S
 - Retrofit capability: gear tray fits into existing 10W Economy Exit EE110M and EE210S base
 - Main body and gear tray only, diffuser not included (can be ordered separately)
 - Low power consumption and LED light source for reduced operation and maintenance costs
 - High temperature NiCad batteries

Catalogue No.
ECOLED

Economy Exit LED - Maintained Body

Description	Dimensions	Photometrics	Spare Parts and Accessories
Economy Exit LED - Maintained Body	Wall Mount: Length: 380mm Width: 110mm (Including Diffuser) Height: 161mm Ceiling Mount: Length: 380mm Width: 161mm (Including Diffuser) Height: 226mm	Wall Mount: C0: E2 C90: E1.5 (Preliminary Results) Ceiling Mount: C0: E2.5 C90: E3.2 (Preliminary Results)	03-01204: Battery 3 Cell Sub-C NiCad Straight 3.6V 1.6Ah 31-PEWM-AU: Diffuser Wall Mount Pictograph 31-PECMS: Diffuser Ceiling Mount Single Sided Pictograph 31-PECMD: Diffuser Ceiling Mount Double Sided Pictograph EEWGWM: Wire Guard Wall Mount EEWGCM: Wire Guard Ceiling Mount

Quickfit LED Exit 75K



- Features**
- Architecturally pleasing slim line design
 - Unique steel Quickfit® mounting bracket that provides strength and enables quick and easy maintenance
 - LED technology 75,000 hours plus lamp life
 - Includes all pictograph diffuser options for single or double sided installation
 - High temperature NiCad batteries
 - Universal wall/ceiling mounting, can also be rod or wire suspended
 - Retrofit capability; fits into any existing Quickfit mounting bracket

Catalogue No.
PQFLEDs

Quickfit LED Exit 75K

Description	Dimensions	Photometrics	Spare Parts and Accessories
Quickfit LED Exit 75K Pictograph	Length: 379mm Width: 72mm Height: 214mm (Including Bracket)	C0: D3.2 C90: D3.2	03-YPMA001: Battery 3 Cell Sub-C NiCad Straight 3.6V 1.6Ah MQFCL: Cantilever Bracket QFWGWM: Wire Guard Wall Mount QFWGCM: Wire Guard Ceiling Mount

Excel LED Quickfit Exit



- Features**
- Architecturally pleasing slim line design
 - Unique steel Quickfit® mounting bracket that provides strength and enables quick and easy maintenance
 - PerpetuLED® LED technology 100,000 hours plus lamp life
 - Includes all pictograph diffuser options for single or double sided installation
 - Advanced PulseTIME® dual rate battery charger with high temperature NiCad batteries
 - Universal wall/ceiling mounting, can also be rod or wire suspended
 - Option - Standard, Nexus® LX monitored or Nexus RF monitored
 - Retrofit capability; fits into any existing Quickfit mounting bracket
 - Frame only available for upgrade of installed product (less mounting bracket and diffusers)
- will accept existing diffusers

Catalogue No.
PQFLED
PQFNXSLED
PQFNRFLED

Excel LED Quickfit Exit

Description	Dimensions	Photometrics	Spare Parts and Accessories
LED Quickfit Pictograph LED Quickfit Nexus LX Pictograph LED Quickfit Nexus RF Pictograph	Length: 379mm Width: 72mm Height: 214mm (Including Bracket)	C0: D3.2 C90: D3.2	03-01218: Battery 4 Cell Sub-C NiCad Straight 4.8V 1.8Ah

For more information and Stanilite's full product range, please refer to the website www.tnbaust.com

Excel LED Quickfit Theatre Mask Exit



Features

- Architecturally pleasing slim line design
- Unique steel Quickfit® mounting bracket that provides strength and enables quick and easy maintenance
- PerpetuLED® LED technology 100,000 hours plus lamp life
- Advanced PulseTIME® dual rate battery charger with high temperature NiCad batteries
- Universal wall/ceiling mounting, can also be rod or wire suspended
- Option - Standard, Nexus® LX monitored or Nexus RF monitored
- Retrofit capability; fits into any existing Quickfit mounting bracket

Catalogue No.

PQFBLED-1
PQFBLED-2
PQFBLED-3
PQFBLED-5
PQFBLED-6

NB: Nexus LX and Nexus

Excel LED Quickfit Theatre Mask Exit

Description

LED Quickfit Theatre Mask SS Picto
LED Quickfit Theatre Mask SS <Picto
LED Quickfit Theatre Mask SS Picto>
LED Quickfit Theatre Mask DS Picto
LED Quickfit Theatre Mask DS AOW Picto

Dimensions

Length: 379mm
Width: 72mm
Height: 214mm
(Including Bracket)

Photometrics

N/A

Spare Parts and Accessories

03-01218: Battery 4 Cell Sub-C NiCad Straight 4.8V 1.8Ah

RF versions also available.

Excel LED Quickfit Weatherproof Exit



Features

- Unique steel Quickfit® mounting bracket that provides strength and enables quick and easy maintenance
- PerpetuLED® LED technology 100,000 hours plus lamp life
- Advanced PulseTIME® dual rate battery charger with high temperature NiCad batteries
- UV stabilised vandal resistant polycarbonate cover or high impact chemical resistant acrylic cover option
- IP65 weatherproof enclosure
- Option - Standard, Nexus® LX monitored or Nexus RF monitored
- Can be wall or ceiling mounted and optional bracket kits available for strengthened wall and cantilever mounting

Catalogue No.

PWQFLED-1
PWQFLED-2
PWQFLED-3
PWQFLED-5
PWQFLED-6

NB: Nexus LX and Nexus
NB: For acrylic option,

Excel LED Quickfit Weatherproof Exit

Description

LED Quickfit Weatherproof SS Polycarbonate Picto
LED Quickfit Weatherproof SS Polycarbonate <Picto
LED Quickfit Weatherproof SS Polycarbonate Picto>
LED Quickfit Weatherproof DS Polycarbonate Picto
LED Quickfit Weatherproof DS Polycarb AOW Picto

Dimensions

Length: 466mm
Width: 155mm
Height: 274mm

Photometrics

C0: D3.2
C90: D3.2

Spare Parts and Accessories

03-01218: Battery 4 Cell Sub-C NiCad Straight 4.8V 1.8Ah
03-02061: Ceiling Bracket Assembly
WQFCLH: Cantilever Mounting Bracket - Heavy Duty
WQFCLL: Cantilever Mounting Bracket - Light Duty
WQFWM: Wall Mount Bracket

RF versions also available.
replace "P" with "A" in the part number.

Excel LED Quickfit Weatherproof Remote Exit



Features

- Used in combination with remote power supply; exit mounted inside the freezer or coolroom and remote power supply mounted outside up to 10m away from the exit (see technical data sheet PSLED1W6 and WPPSLED1W6, available on the website)
- Unique steel Quickfit® mounting bracket that provides strength and enables quick and easy maintenance
- PerpetuLED® LED technology 100,000 hours plus lamp life
- Advanced PulseTIME® dual rate battery charger with high temperature NiCad batteries
- UV stabilised vandal resistant polycarbonate cover
- IP65 weatherproof enclosure
- Increased safety and no shock hazard by isolating the AC primary circuits from the unit
- Includes all pictograph diffuser options for single or double sided installation
- Can be wall or ceiling mounted and optional bracket kits available for strengthened wall and cantilever mounting
- Ideal for freezer or coolroom applications up to -30°C
- Remote power supply available in both Nexus® LX and Nexus RF configurations.

Catalogue No.

PWQFFRLED-1

Excel LED Quickfit Weatherproof Remote Exit

Description

LED Quickfit Weatherproof Remote Pictograph

Dimensions

Length: 466mm
Width: 155mm
Height: 274mm

Photometrics

C0: D3.2
C90: D3.2

Spare Parts and Accessories

03-01218: Battery 4 Cell Sub-C NiCad Straight 4.8V 1.8Ah
03-02061: Ceiling Bracket Assembly
WQFCLH: Cantilever Mounting Bracket - Heavy Duty
WQFCLL: Cantilever Mounting Bracket - Light Duty
WQFWM: Wall Mount Bracket

Excel LED Quickfit Vandal Resistant Exit



Features

- IK9 mechanical impact resistance
- Vermin resistance
- Unique internal steel slide connect bracket that provides strength, enables quick and easy maintenance
- Strong steel body and end cap
- Anti-tamper cover screws
- PerpetuLED® LED technology 100,000 hours plus lamp life
- Advanced PulseTIME® dual rate battery charger with high temperature NiCad batteries
- Universal wall/ceiling mounting
- Includes all pictograph diffuser options for single or double sided installation
- Option - Standard, Nexus® LX monitored or Nexus RF monitored

Catalogue No.

VPQLED
VPQNXSLED
VPQNRFLED

Excel LED Quickfit Vandal Resistant Exit

Description

LED Quickfit Vandal Resistant Pictograph
LED Quickfit Vandal Resistant Nexus LX Pictograph
LED Quickfit Vandal Resistant Nexus RF Pictograph

Dimensions

Length: 410mm
Width: 140mm
Height: 265mm

Photometrics

C0: E1.25
C90: E1.25
(Preliminary Results)

Spare Parts and Accessories

03-01218: Battery 4 Cell Sub-C NiCad Straight 4.8V 1.8Ah
PQFLED-FR: LED Quickfit Frame Only
PQFNXSLED-FR: LED Quickfit Nexus LX Frame Only
PQFNRFLED-FR: LED Quickfit Nexus RF Frame Only

For more information and Stanilite's full product range, please refer to the website www.tnbaust.com

Excel LED Legend Quickfit Exit



Features

- Architecturally pleasing slim line design
- Unique steel slide connect bracket that provides strength and enables quick and easy maintenance
- LED technology 50,000 hours lamp life
- High emergency classification
- Includes all pictograph diffuser options
- Advanced dual rate battery charger with high temperature NiMH batteries
- Universal wall/ceiling mounting, can also be rod or wire suspended
- Option - Standard, Nexus® LX monitored or Nexus RF monitored
- Retrofit capability; fits into any existing Quickfit® mounting bracket

Catalogue No.

PLQLED
PLQNXSLED
PLQNRFLLED

Excel LED Legend Quickfit Exit

Description

LED Legend Quickfit Pictograph
LED Legend Quickfit Nexus LX Pictograph
LED Legend Quickfit Nexus RF Pictograph

Dimensions

Length: 379mm
Width: 72mm
Height: 232mm
(Including Bracket)

Photometrics

C0: D3.2
C90: E2

Spare Parts and Accessories

03-01213P: Battery 4 Cell AA NiMH Side by Side 4.8V 1.25Ah

Excel LED Legend Recessed Exit



Features

- Architecturally pleasing slim line design
- One-box solution, overall light weight and snap n clip mechanism allows for quick and easy installation
- Suits ceiling thickness 1mm - 19mm
- LED technology 50,000 hours lamp life
- High emergency classification
- 2m flex & plug included
- Includes all pictograph diffuser options
- Option - Standard, Nexus® LX monitored or Nexus RF monitored

Catalogue No.

PLRLED
PLRNXSLED
PLRNRFLLED

Excel LED Legend Recessed Exit

Description

LED Legend Recessed Pictograph
LED Legend Recessed Nexus LX Pictograph
LED Legend Recessed Nexus RF Pictograph

Dimensions

Length: 370mm
Width: 120mm
Height: 164mm
(Including Face Plate)

Photometrics

C0: D3.2
C90: E2

Spare Parts and Accessories

03-01213P: Battery 4 Cell AA NiMH Side by Side 4.8V 1.25Ah
PLRLEDADAPTOR: Cover Plate LED Legend Recessed Retrofitting

Excel LED Legend Recessed Exit, Original Style Square Diffuser



Features

- Slim and elegant
- Surface ceiling mounted
- LED technology 50,000 hours plus lamp life
- Advanced PulseTIME® dual rate battery charger with high temperature NiMH batteries
- Easy installation and maintenance
- 2m flex & plug included
- Option - Standard, Nexus® LX monitored or Nexus RF monitored
- All pictograph diffuser options available (order separately)

Catalogue No.

PLROLED
PLRONXSLED
PLRONRFLLED

Excel LED Legend Recessed Exit, Original Style Square Diffuser

Description

LED Legend Recessed, Original Style Square Diffuser
LED Legend Recessed Nexus LX, Original Style Sq Diff
LED Legend Recessed Nexus RF, Original Style Sq Diff

Dimensions

Face Plate:
Length: 464mm
Width: 121mm

Ceiling Cutout:
Length: 422mm
Width: 93mm

Photometrics

C0: D2
C90: E1.6

Spare Parts and Accessories

03-01213P: Battery 4 Cell AA NiMH Side by Side 4.8V 1.25Ah
31-PL1: Diffuser Single Sided Picto
31-PL2: Diffuser Single Sided <Picto
31-PL3: Diffuser Single Sided Picto>
31-PL5: Diffuser Double Sided Picto
31-PL6: Diffuser Double Sided Picto AOW

Excel LED Legend Surface Mount Exit



Features

- Architecturally pleasing slim line design
- One-box solution, overall light weight and snap n clip mechanism allows for quick and easy installation
- Surface mounted - suitable for ceilings where a recessed fitting is not feasible
- LED technology 50,000 hours lamp life
- High emergency classification
- Includes all pictograph diffuser options
- Suspended, wall and cantilever mounting kit options available
- Option - Standard, Nexus® LX monitored or Nexus RF monitored

Catalogue No.

PLSLED
PLSNXSLED
PLSNRFLLED

Excel LED Legend Surface Mount Exit

Description

LED Legend Surface Mount Pictograph
LED Legend Surface Mount Nexus LX Pictograph
LED Legend Surface Mount Nexus RF Pictograph

Dimensions

Length: 375.5mm
Width: 79.0mm
Height: 220.0mm

Photometrics

C0: D3.2
C90: E2

Spare Parts and Accessories

03-01213P: Battery 4 Cell AA NiMH Side by Side 4.8V 1.25Ah
PLSLEDCLKIT: Cantilever Mounting Kit
PLSLEDWMKIT: Wall Mounting Kit

For more information and Stanilite's full product range, please refer to the website www.tnbaust.com

Excel LED Legend Wall Mount Flush Exit



Features

- Slim, elegant and easy to maintain
- LED technology 50,000 hours plus lamp life
- Large terminal block (16mm²) for easy wiring
- Advanced PulseTIME® dual rate battery charger with high temperature NiMH batteries
- Cable entry at either end of base
- Option - Standard, Nexus® LX monitored or Nexus RF monitored

Catalogue No.

PLRWLED-1
PLRWLED-2
PLRWLED-3
PLRWNXSLED-1
PLRWNXSLED-2
PLRWNXSLED-3
PLRWNRFLED-1
PLRWNRFLED-2
PLRWNRFLED-3

Excel LED Legend Wall Mount Flush Exit

Description

LED Legend Wall Mount Flush Picto Diffuser
LED Legend Wall Mount Flush <Picto Diffuser
LED Legend Wall Mount Flush Picto> Diffuser
LED Legend Wall Mount Flush Nexus LX Picto Diffuser
LED Legend Wall Mount Flush Nexus LX <Picto Diffuser
LED Legend Wall Mount Flush Nexus LX Picto> Diffuser
LED Legend Wall Mount Flush Nexus RF Picto Diffuser
LED Legend Wall Mount Flush Nexus RF <Picto Diffuser
LED Legend Wall Mount Flush Nexus RF Picto> Diffuser

Dimensions

Face Plate:
Length: 388mm
Width: 212mm

Photometrics

N/A

Spare Parts and Accessories

03-01213P: Battery 4 Cell AA NiMH Side by Side 4.8V 1.25Ah

Excel LED Jumbo Exit



Features

- Architecturally pleasing and lightweight design
- 50,000 hour rated 8W LED lamp, 2 year warranty
- High emergency classification
- Available in all pictograph diffuser options
- High temperature NiCad batteries
- Wall mount or ceiling/suspended mount versions available to cover all installation requirements
- Large terminal (16mm2) block for easy wiring
- Option - Standard, Nexus® LX monitored or Nexus RF monitored
- Viewing distance 40m
- Protective wire guard available - ceiling/suspended mount and wall mount

Catalogue No.

PEJLEDMWM-1
PEJLEDMWM-2
PEJLEDMWM-3
PEJLEDMCM-1
PEJLEDMCM-2
PEJLEDMCM-3
PEJLEDMCM-5
PEJLEDMCM-6

NB: Nexus LX and Nexus

Excel LED Jumbo Exit

Description

LED Jumbo Maintained SS Picto Wall Mount
LED Jumbo Maintained SS <Picto Wall Mount
LED Jumbo Maintained SS Picto> Wall Mount
LED Jumbo Maintained SS Picto Ceiling Mount
LED Jumbo Maintained SS <Picto Ceiling Mount
LED Jumbo Maintained SS Picto> Ceiling Mount
LED Jumbo Maintained DS Picto Ceiling Mount
LED Jumbo Maintained DS Picto AOW Ceiling Mount

Dimensions

Length: 615mm
Width: 123mm
Height: 310mm

Photometrics

C0: D4
C90: E2.5
(Preliminary Results)

Spare Parts and Accessories

03-01015P: Battery 3 Cell D NiCad Straight 3.6V 4.0Ah
15-10022: LED Tube 8W 5700K 600mm

RF versions also available.

Excel LED Quickfit Vandal Resistant Jumbo Exit



Features

- IK9 mechanical impact resistance
- Unique internal steel slide connect bracket that provides strength, enables quick and easy maintenance
- Strong steel body and end cap
- Anti-tamper cover screws
- LED technology 50,000 hours plus lamp life
- High temperature NiCad batteries
- Universal wall/ceiling mounting
- Option - Standard, Nexus® LX monitored or Nexus RF monitored
- Viewing distance 40m

Catalogue No.

VPQJLED-1
VPQJLED-2
VPQJLED-3
VPQJLED-5
VPQJLED-6

NB: Nexus LX and Nexus

Excel LED Quickfit Vandal Resistant Jumbo Exit

Description

LED Quickfit Vandal Resistant Jumbo SS Picto
LED Quickfit Vandal Resistant Jumbo SS <Picto
LED Quickfit Vandal Resistant Jumbo SS Picto>
LED Quickfit Vandal Resistant Jumbo DS Picto
LED Quickfit Vandal Resistant Jumbo DS Picto AOW

Dimensions

Length: 647mm
Width: 140mm
Height: 450mm

Photometrics

N/A

Spare Parts and Accessories

03-01015P: Battery 3 Cell D NiCad Straight 3.6V 4.0Ah
15-10022: LED Tube 8W 5700K 600mm

RF versions also available.

For more information and Stanilite's full product range, please refer to the website www.tnbaust.com