

## CLEVERTRONICS LIFELIGHT PRO CYLINDER SURFACE MOUNT EMERGENCY



### PRODUCT INFORMATION

Catalogue Number	LLIFE-PRO-SMC-ZW-BLK
Description	Lifelight PRO, High Performance, Cylinder Surface Mount Emergency Light with Lithium Battery Technology
Mounting	Surface Mount
Dimensions L x W x H	128mm (D), 252mm (L)
Ceiling hole cut-out	N/A
Minimum ceiling depth	N/A
Operating Mode	Non-Maintained
Testing System	Zoneworks Computerised Testing
Ballast	N/A
Charging Method	Intelligent current limited constant voltage charger
Lamps(s)	2 x 3W LED (Lifetime warranty on the lamp head and loom assembly) No dome cover required
Operating Voltage	240V 50Hz
Power Consumption	0.4 Watts
IP Rating	IP20
Impact Rating	N/A
Operating Temperature	1° to 40°C (Ambient)
AS/NZ2293 Classification	C <sub>0</sub> =D50 C <sub>90</sub> =D50

### REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1100835	2 x 3W LED Round Head Assembly - Black
1530230	Battery, 3.3V 5Ah.Li-ion, 200mm lead with Bracket
8002390	Driver, PCA:Lifelight Pro, Zoneworks Compatible
8001450	Zoneworks Powerline Node