

# Nipper Emergency

Versatile fluorescent batten with multiple options designed for use in general commercial interiors.

## Specification

- Energy efficient lamps 18W and 36W fluorescent
- End to end mounting
- Maintained, Non-maintained and Sustained available
- Quarter turn
- 'quick release' reflector and Quick release diffuser end cap
- Large 3 way tunnel terminal block
- Rolled cable entry - no grommets required
- Wide body version width is designed to cover flush mount junction box installations
- Wire guards, reflectors and industrial options available
- Compliant to AS/NZS2293

## Product Codes

Code	Version	Dim (mm)	Mass (kg)
PN136MEL	1 x 36W Comb. Maint. Bare	1229 x 52 x 92	3.4
PN136NM	1 x 36W Non-Maint. Bare	1229 x 52 x 92	3.4
PN218MEL	2 x 18W Comb. Maint. Bare	619 x 102 x 94	3.0
PN236MEL	2 x 36W Maint. Bare	1229 x 102 x 101	3.4
PND136MEL	1 x 36W Maint. Diffused	1229 x 52 x 97	3.4
PND218MEL	2 x 18W Maint. Diffused	619 x 102 x 101	3.0
PND236MEL	2 x 36W Comb.Maint. Diffused	1229 x 52 x 92	3.4
Accessories			
BP4S	Battery 4.8V NiCad, 4cell		



## Quick Specification

Pierlite Nipper Bare Batten Emergency single and twin 18W/36W , slim line body profile. Captive cover plate 1/4 turn clip and end to end mounting. Compliant to AS/NZS2293

## Design Application

Domestic, retail stores and outlets, garages, food processing areas, change rooms and general commercial areas.

## Performance

Product Code		Classification	Mounting Height in Metres										
			2.1	2.4	2.7	3	3.6	4	4.5	5	6	8	10
PN118NM	C0	D32	15.4	16.1	16.7	17.2	18	18.5	19.1	19.5	20.2	20.7	20.3
	C90	C32	10	10.7	11.3	11.8	12.8	13.4	14	14.5	15.4	16.4	16.5
PN218MEL	C0	D32	15.4	16.1	16.7	17.2	18	18.5	19.1	19.5	20.2	20.7	20.3
	C90	C32	10	10.7	11.3	11.8	12.8	13.4	14	14.5	15.4	16.4	16.5
	180	D25	14.2	14.7	15.3	15.7	16.5	16.9	17.3	17.7	18.1	18.2	17.3
PN136NM	C0	D40	16.7	17.4	18	18.6	19.6	20.1	20.8	21.3	22.1	23	23.1
	C90	C40	10.6	11.3	11	12.6	13.6	14.3	15	15.6	16.6	17.9	18.5
PN136MEL	C0	D40	16.7	17.4	18	18.6	19.6	20.1	20.8	21.3	22.1	23	23.1
	C90	C40	10.6	11.3	11	12.6	13.6	14.3	15	15.6	16.6	17.9	18.5
PN236MEL	C0	D40	16.7	17.4	18	18.6	19.6	20.1	20.8	21.3	22.1	23	23.1
	C90	C40	10.6	11.3	11	12.6	13.6	14.3	15	15.6	16.6	17.9	18.5
	180	D40	16.7	17.4	18	18.6	19.6	20.1	20.8	21.3	22.1	23	23.1

IP20



Max Dim (mm)  
1229 x 52 x 92

PDF Prepared: 10.03.2017 07:03am, Last page update: Jun 2015

