

Insulated loadcentres DIN-T – surface mount

- Standard AS/NZS 3439-3
- Suits NHP Din-T MCBs and associated DIN equipment
- Surface mount
- Degree of protection IP 40
- Split earth neutral bars
- Removable earth and neutral bar support
- Transparent or white door
- Door hinged at the top
- Supplied complete with Buscomb



Surface mount

Pole capacity	No. of rows	Neutral bar	Earth bar	Trans. door Cat. No.	White door Cat. No.
12	1	5/3/3	12	CSB12ST	CSB12SW
18	1	9/3/3/3	18	CSB18ST	CSB18SW
24	2	10/3/3/3/3	24	CSB24ST	CSB24SW
36	3	12/12/12	36	CSB36ST	CSB36SW

Neutral bar kit

Pole capacity	Neutral bar	Cat. No.
36	11/3/3/3/3/3/3	CSBN36S

Dimensions Surface mount

Pole capacity	Width (mm)	Height (mm)	Depth (mm)
12	256	200	97
18	363	220	97
24	269	326	97
36	306	473	102

Insulated loadcentres

DIN-T – flush mount

- Standard AS/NZS 3439-3
- Suits NHP Din-T MCBs and associated DIN equipment
- Surface mount
- Degree of protection IP 40
- Split earth neutral bars
- Removable earth and neutral bar support
- Transparent or white door
- Door hinged at the top
- Supplied complete with Buscomb



Flush mount

Pole capacity	No. of rows	Neutral bar	Earth bar	Trans. door Cat. No.	White door Cat. No.
12	1	5/3/3	12	CSB12FT	CSB12FW
18	1	9/3/3/3	18	CSB18FT	CSB18FW
24	2	10/3/3/3/3	24	CSB24FT	CSB24FW
36	3	12/12/12	36	CSB36FT	CSB36FW

Neutral bar kit

Pole capacity	Neutral bar	Cat. No.
36	11/3/3/3/3/3/3	CSBN36F

Metal backing plate

Pole capacity	Cat. No.
12	CSB12FMP
18	CSB18FMP
24	CSB24FMP
36	CSB36FMP

Flush mount

Pole capacity	Description	Width (mm)	Height (mm)	Depth (mm)
12	Base	270	211	66
12	Cover	304	246	29
18	Base	380	232	76
18	Cover	412	267	29
24	Base	270	304	76
24	Cover	305	358	29
36	Base	308	470	76
36	Cover	342	503	29

Flush enclosure - cut out dimensions

Enclosure type	Width (mm)	Height (mm)
12 way	258	199
18 way	366	216
24 way	258	311
36 way	294	458