



CLEVERTRONICS LP LIFELIGHT PRO (DALI)



PRODUCT INFORMATION

Catalogue Number	CLIFE-PRO-DALI
Description	LP Premium LifeLight PRO, High Performance, Recessed Emergency Light with Lithium Battery Technology
Mounting	Recessed mount
Dimensions L x W x H	232mm x 40mm x 40mm (Control Pack) , 60mm Head Diameter (95mm with adaptor plate)
Ceiling hole cut-out	51mm, 85mm (with adaptor plate)
Minimum ceiling depth	200mm, 120mm (with adaptor plate)
Operating Mode	Non-maintained
Testing System	DALI compatible
Charging Method	Intelligent Current Limited Constant Voltage
Lamp(s)	2 x 3W LED (Lifetime warranty on the lamp head and loom assembly)
Operating Voltage	240V AC; 50Hz
Power Consumption	0.4 Watts (Standby)
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C ₀ =D63 C ₉₀ =D63

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550230	BATT:LP 3.2V 6400mAh.200mm lead.Brkt.
CLIFE-PRO-CKIT	Lifelight Pro, Control Only, LP Lithium
1100833	Lifelight Pro Head Assbly,Rnd,Large+Ring
8002200	PCA:DALI Node, #CT10410-A3

DALI EM

LP LITHIUM IRON
PHOSPHATE
PREMIUM
PROVEN PROJECT PERFORMANCE