



CLEVERTRONICS L10 OPTIMUM LIFELIGHT PRO EMERGENCY WITH IP66/67 LAMP HEAD (ZONeworks)



Lifelight Pro WP Lamp Head

PRODUCT INFORMATION

Catalogue Number	LLIFE-PRO-WP-ZW
Description	Lifelight PRO, High Performance, Recessed Emergency Light with Lithium Battery Technology and IP66/67 Head
Mounting	Surface Mount Head
Dimensions L x W x H	232mm x 40mm x 40mm (Control Pack) , 122mm x 120mm x 75mm (IP66/67 Lamp Head Enclosure)
Ceiling hole cut-out	N/A
Minimum ceiling depth	N/A
Operating Mode	Non-Maintained
Testing System	Zoneworks Computerised Testing
Ballast	N/A
Charging Method	Intelligent current limited constant voltage charger
Lamps(s)	2 x 3W LED (Lifetime warranty on the lamp head and loom assembly) No dome cover required
Operating Voltage	240V 50Hz
Power Consumption	0.4W (standby) 2.2W (max during 16 hour charge)
IP Rating	IP66/67 Lamp Head Enclosure
Impact Rating	IK08 (Lamp Enclosure)
Operating Temperature	1° to 40°C (ambient for battery and control gear) -40°C to 40°C (ambient for weatherproof lamp head)
AS/NZ2293 Classification	C ₀ =D40 C ₉₀ =D40

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1100830	Lamps: 2 x 3W LED Round Head Assembly - White
2750070	IP66/67 Lamp Head Enclosure, C/W Clear Lid
1530230	Battery: 3.3V 5Ah.Li-ion, 200mm lead with Bracket
LLIFE-PRO-CKIT	PCA: Lifelight Pro Control Gear
8001450	PCA: Zoneworks Powerline Node, #CT10310-A6

ZONeworks®