

# PRODUCT DATASHEET

## DULUX D/E 26 W/4000K G24q-3

OSRAM DULUX D/E | CFLni, 2 tubes, with 4-pin base for ECG operation



---

### AREAS OF APPLICATION

- Offices, public buildings
- Shops
- Supermarkets and department stores
- Hotels, restaurants
- Industry

---

### PRODUCT BENEFITS

- Extremely economical
- Good quality of light

---

### PRODUCT FEATURES

- Short and compact pin-base lamp with double-turn tubes
- Single-ended four-pin plug-in G24q base



**TECHNICAL DATA**


Electrical data

<b>Rated wattage</b>	26.00 W
<b>Nominal wattage</b>	26.00 W

Photometrical data

<b>Nominal luminous flux</b>	1800 lm
<b>Rated luminous flux</b>	1800 lm
<b>Rated color temperature</b>	4000 K
<b>Color rendering index Ra</b>	≥80
<b>Rated LLMF at 2,000 h</b>	0.90
<b>Rated LLMF at 4,000 h</b>	0.84
<b>Rated LLMF at 6,000 h</b>	0.83
<b>Rated LLMF at 8,000 h</b>	0.81
<b>Color temperature</b>	4000 K
<b>Luminous flux</b>	1800 lm
<b>Color rendering index Ra</b>	≥80

Dimensions & weight



<b>Diameter</b>	12.0 mm
<b>Overall length</b>	163.0 mm
<b>Length</b>	165.0 mm
<b>Outer bulb</b>	T12
<b>Maximum diameter</b>	11.0 mm

Lifespan

<b>Nominal lamp life time</b>	10000 h
<b>Rated lamp life time</b>	10000 h
<b>Rated lamp survival factor at 2,000 h</b>	0.99

Rated lamp survival factor at 4,000 h	0.99
Rated lamp survival factor at 6,000 h	0.95
Rated lamp survival factor at 8,000 h	0.81
Operation mode LLMF/LSF	HF

#### Additional product data

Base (standard designation)	G24q-3
Mercury content	1.3 mg

#### Capabilities

Suitable for indoor	Yes
---------------------	-----

#### Certificates & standards

Energy consumption	29 kWh/1000h
Energy efficiency class	A

### EQUIPMENT / ACCESSORIES

- Suitable for operation on electronic control gear

### SAFETY ADVICE

In case of lamp breakage: [www.ledvance.com/brokenlamp](http://www.ledvance.com/brokenlamp)

### LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4008321830517	Folding carton box 1	36 mm x 36 mm x 179 mm	59.00 g	0.23 dm <sup>3</sup>
4008321830524	Shipping carton box 10	187 mm x 81 mm x 196 mm	662.00 g	2.97 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

### DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.