



## CLEVERTRONICS L10 OPTIMUM LIFELIGHT RECESSED EMERGENCY (DALI)



### PRODUCT INFORMATION

Catalogue Number	LLIFE-DALI
Description	Lifelight, High Performance, Recessed Emergency Light with Lithium Battery Technology
Mounting	Recessed Ceiling
Dimensions L x W x H	232mm x 51mm x 42mm (Control Pack) , 95mm Head Diameter (145mm with adaptor plate)
Ceiling hole cut-out	85mm, 135mm (with adaptor plate)
Minimum ceiling depth	120mm, 70mm (with adaptor plate)
Operating Mode	Non-Maintained
Testing System	DALI Compatible
Ballast	N/A
Charging Method	Intelligent current limited constant voltage charger
Lamps(s)	1 x 3W LED (Lifetime warranty on the lamp head and loom assembly) No dome cover required
Operating Voltage	240V 50Hz
Power Consumption	1.3W (standby) 3W (max during 16 hour charge)
IP Rating	IP20
Impact Rating	N/A
Operating Temperature	1° to 40°C (Ambient)
AS/NZ2293 Classification	C <sub>0</sub> =D32 C <sub>90</sub> =D32

### REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1100860	Lamps: 1 x 3W LED Round Head Assembly & Ring - White
1530010	Battery: 3.3V 2.5Ah, Li-ion, 200mm lead with Bracket
LLIFE-CKIT	PCA: L10 Lifelight Control Gear
8002200	PCA: DALI Node, #CT10410-A3

