



Main

Range of product	Back-UPS SX3
Product or component type	Uninterruptible power supply (UPS)
Battery type	Lead-acid battery

Complementary

Energy values	273 J
Topology	Line interactive
Type of signal	Stepped approximation to a sinewave
Input voltage	230 V 150...280 V for mains operation
Output voltage	230 V (+/- 8 %) on battery mode
Protection type	7 A circuit breaker protection
Transfer time	8 ms (typical) 10 ms (maximum)
Output frequency	50 Hz (+/- 1 Hz) 60 Hz (+/- 1 Hz)
Power range	480 W (output) 800 VA (output)
Electrical connection	1 outlet (input) IEC 320 C14 6 outlet (output) IEC 320 C13
Local signalling	Alarm (low battery) LED (on battery)
Cable length	1.16 m
Number of cables	1
Number of batteries	1
Charging time	8 h
Battery capacity	76 Ah
Colour	Black
Product weight	8 kg
Height	215 mm
Width	130 mm
Depth	336 mm

Environment

acoustic level	< 45 dBA at 1 m
relative humidity	0...95 % non-condensing (operating) 0...95 % non-condensing (storage)
operating altitude	0...3000 m
storage altitude	0...15000 m
ambient air temperature for operation	0...40 °C
ambient air temperature for storage	-15...40 °C
standards	EN/IEC 60950-1
product certifications	CE GOST NEMKO

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

