



CSB surface mount loadcentre, 18way, transparent door

- Standard AS/NZS 3439-3
- Suit MOD6 MCBs, RCDs & RCBOs
- IP40 rating
- Split neutral and earth bars rated 100A
- Removable earth and neutral bar
- White or transparent door
- Door hinged at the top
- Supplied complete with busbar comb
- Base (ABS)
- Door (white -ABS), (transparent (polycarbonate))
- 8way- Neutral split 4/4 & 8way earth, 12way- Neutral split 5/3/3 & 12way earth
- 18way- Neutral split 9/3/3/3 & 18way earth, 24way- Neutral split 10/3/3/3/3 & 24way earth
- 36way- Neutral split 12/12/12 & 36way earth

Representative Photo Only
(actual product may vary based on configuration selections)

SPECIFICATIONS	
Component Type	Power Distribution & Protection
Component Type	Loadcentre Enclosure
Item Description	CSB surface mount loadcentre, 18way, transparent door
IP rating	IP40
Number of Poles	18
MCB Type	DIN Profile
Material, body / housing	ABS (Acrylonitrile Butadiene Styrene)
Colour, body / housing	White
Colour, door	Clear / Transparent
Ue, rated operational voltage, AC, 3ph, nom	415
Ue, rated operational voltage, AC, 1ph, nom	240
In, rated current	100
In, rated current, busbar comb, centre feed	130
In, rated current, busbar comb, end feed	80
Tunnels, neutral bar	9/3/3/3
Tunnels, earth bar	18
Mounting	Surface Mount
Height	220
Width	363
Depth	97
zzzEarth and Neutral bar Rating	100A 16 mm tunnel terminals
Standards Compliance	AS/NZS 3439.3

Catalogue No: **CSB18ST**

LOADCENTRE 18 WAY DIN SURFACE TRANSPARENT DOOR

Power Distribution and Protection > Distribution Boards > Loadcentre Assemblies > MOD6 Range of Loadcentres > MOD6 CSB Loadcentres > Insulated Surface Mount Transparent Door



REFERENCES

IECEX Certificate -

Supplier Declaration of
Conformity: -

Installation Guide: -

User Manual: -

Manufacturer Datasheet: -

Manufacturer Catalogue
& Product Selection: -