



WBMDUR

Mechanism rotary dimmer trailing-edge

Technical characteristics

Main electrical features

Frequency	50 Hz
-----------	-------

Voltage

Operating voltage	230 V~ +10%/-15%
-------------------	------------------

Fuse

Fuse	short-circuit and overload proof (electronic fuse)
------	--

Dimensions

Depth	65 mm
Height	24 mm
Width	24 mm

Power

Power consumption (standby)	max. 0.1 W
Electronic transformers	20...350 W

Measurement

Extension unit input	with extension unit input for slave push-button WBMSLL
----------------------	---

LED control

Dimmable 230 V LED lamps	2.5...250 W
--------------------------	-------------

Incandescent bulbs control

230 V incandescent lamps and halogen lamps	7...300 W
--	-----------

Installation, mounting

Installation mode	RotoLoc ®
-------------------	-----------

Connection

Conductor cross-section	1.5 mm ²
-------------------------	---------------------

Cable

Cable length, extensions	max. 20 m
--------------------------	-----------

Equipment

On/Off switch	Yes
Dimming principle	phase cut-off
Brightness	with brightness memory

Use conditions	
Operating temperature	-5...50 °C
Storage/transport temperature	-20...70 °C
Temperature	with overheating protection
Identification	
Main design line	Mechanisms
meta_keyword	Dimmer;Switch;Regulator;Controller;Rheostat;