

2000 Series Horizontal Switched Socket Outlets

Specifications

Operational Voltage: 250V a.c. 50Hz
Maximum Load: 10A
AS/NZS 3112
Standard Colours: WE - White Electric, CM - Cream, BK - Black





Applications

Recommended for residential and commercial environments, the 2000 Series is a combination of beautiful design, refinement and reliable performance.

Features

- Available in single and twin variants
- Extra switch variants
- Operational safety shutters and/or neons
- Double pole variants
- Available in 10A, 15A and 20A
- Horizontal mount
- 84mm mounting centres
- Terminals suit 4 x 2.5mm² cable
- Metal cover finishes: GD - Gold, BA - Brushed Aluminium, CH - Chrome, GP - Gold Plate and SP - Silver Plate (available on some models).

Dimensions



Cleaning Guidelines

It is not recommended to spray cleaning products directly on to electrical switches. Before cleaning, ensure that switches are isolated (switched off). Do not use any cleaning sprays - only wipe down with damp or dry cloth.

Ordering Guide

2000 Series

Horizontal Switched Socket Outlets

STANDARD SIZE SINGLE SWITCHED SOCKETS - HORIZONTAL MOUNTING				
Cat. No.	Length	Width	Depth	Mounting Centres
All Products	116mm	76mm	28mm	84mm
2015	Single Switched Socket Outlet, 250V/10A			
2015S	Single Switched Socket Outlet, 250V/10A, with safety shutter			
2015N	Single Switched Socket Outlet, 250V/10A, with safety shutter and neon			
2015D	Single Switched Socket Outlet, 250V/10A, double pole			
2015L	Single Switched Socket Outlet, 250V/10A, with round earth pin for lighting			
2015/15	Single Switched Socket Outlet, 250V/15A			
2015/15N	Single Switched Socket Outlet, 250V/15A, with safety shutter and neon			
2015/20	Single Switched Socket Outlet, 250V/20A			
2015X	Single Switched Socket Outlet, 250V/10A, with removable extra switch			
2015XN	Single Switched Socket Outlet, 250V/10A, with safety shutter, neon and removable extra switch			
2015XS	Single Switched Socket Outlet, 250V/10A, with safety shutter and removable extra switch			
2015XUA	Single Switched Socket Outlet, 250V/10A, with extra switch aperture, less mechanism			
2015XX	Single Switched Socket Outlet, 250V/10A, with two removable extra switches			

STANDARD SIZE TWIN SWITCHED SOCKETS - HORIZONTAL MOUNTING				
Cat. No.	Length	Width	Depth	Mounting Centres
All Products	116mm	76mm	28mm	84mm
2025	Twin Switched Socket Outlet, 250V/10A			
2025S	Twin Switched Socket Outlet, 250V/10A, with safety shutter			
2025N	Twin Switched Socket Outlet, 250V/10A, with safety shutter and neon			
2025D	Twin Switched Socket Outlet, 250V/10A, double pole			
2025D15	Twin Switched Socket Outlet, 250V/15A, double pole			
2025DN	Twin Switched Socket Outlet, 250V/10A, with safety shutter and neon, double pole			
2025L	Twin Switched Socket Outlet, 250V/10A, with round earth pin for lighting			
2025/15	Twin Switched Socket Outlet, 250V/15A			
2025QC	Twin Switched Socket Outlet, 250V/10A, Quick Connect			
2025XA	Twin Switched Socket Outlet, 250V/10A, with removable extra switch			
2025XN	Twin Switched Socket Outlet, 250V/10A, with safety shutter, neon and removable extra switch			
2025XAS	Twin Switched Socket Outlet, 250V/10A, with safety shutter and removable extra switch			
2025XUA	Twin Switched Socket Outlet, 250V/10A, with extra switch aperture, less mechanism			

Schneider Electric (Australia) Pty Ltd

33-37 Port Wakefield Road,
Gepps Cross, South Australia 5094

Contact us clipsal.com/feedback

National Customer Care Enquiries:
1300 2025 25

clipsal.com

Schneider Electric (Australia) Pty Ltd reserves the right to change specifications, modify designs and discontinue items without incurring obligation and whilst every effort is made to ensure that descriptions, specifications and other information in this document are correct, no warranty is given in respect thereof and the company shall not be liable for any error therein.

© 2014 Schneider Electric. All Rights Reserved.

Trademarks are owned by Schneider Electric Industries SAS or its affiliated companies.