

MASTER TL-D Super 80

TL-D 18W/840 1SL/25

The MASTER TL-D Super 80 lamp offers more lumens per watt and better color rendering than TL-D standard colors. Furthermore, it has a lower mercury content. The lamp can be operated in existing TL-D luminaires.

Warnings and Safety

- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.


Product data

General Information		Controls and Dimming	
Cap-Base	G13 [Medium Bi-Pin Fluorescent]	Dimmable	Yes
Life to 50% Failures (Nom)	13,000 hour(s)		
Light Technical		Mechanical and Housing	
Color Code	840 [CCT of 4000K]	Bulb Shape	T8 [26 mm (T8)]
Color Designation	Cool White (CW)		
Correlated Color Temperature (Nom)	4000 K	Approval and Application	
Luminous Efficacy (rated) (Nom)	75 lm/W	Mercury (Hg) Content (Nom)	2.0 mg
Color rendering index (CRI)	82		
Operating and Electrical		Product Data	
Power Consumption	18 W	Full product code	871829125414000
Lamp Current (Nom)	0.360 A	Order product name	TL-D 18W/840 1SL/25
Voltage (Nom)	59 V	Order code	927981184024
Voltage (Nom)	59 V	Numerator - Quantity Per Pack	1
		Numerator - Packs per outer box	25
		Material Nr. (12NC)	927981184024
		Full product name	TL-D 18W/840 1SL/25

MASTER TL-D Super 80



EAN/UPC - Case	8718291254157
EAN/UPC - Product/Case	8718291254140

Dimensional drawing




Product	D (max)	A (max)	B (max)	B (min)	C (max)
TL-D 18W/840 1SL/25	28 mm	589.8 mm	596.9 mm	594.5 mm	604 mm

Lifetime



Life Expectancy Diagram - TL-D 18W/840 1SL/25

Life Expectancy Diagram - TL-D 18W/840 1SL/25



Lumen Maintenance Diagram - TL-D 18W/840 1SL/25

MASTER TL-D Super 80

