



LIFESAVER

9 VOLT

PHOTOELECTRIC SMOKE ALARMS

**SENSITIVE TO SLOW
SMOULDERING FIRES**



*“Choose **PSA** for smoke alarms”*



LIFESAVER

9V PHOTOELECTRIC SMOKE ALARM

Model LIFPE9/1 and LIFPE9M

Features:

- ✓ Photoelectric sensor suitable for slow smouldering fires
- ✓ Insect screen protection over sensor
- ✓ Slim-line compact size
- ✓ Red led light for alarm indication and testing
- ✓ Mute & alarm test button (LIFPE9M)
- ✓ Alarm test button (LIFPE9/1)
- ✓ Low battery warning signal
- ✓ Mounting screws supplied
- ✓ Anti-tamper locking feature
- ✓ Easy twist on twist off installation
- ✓ Complies & Approved to Australian Standard AS3786
- ✓ Loud 85db alarm

Specification:

Power Source:	9V Battery
Battery Type:	Eveready 1222 Energizer 522 Gold Peak 1604S Duracell MN 1604 Ultralife U9VL
Operating Temp:	0°C to 45°C
Ambient Humidity:	10%-90%
Alarm Sound Level:	85 Decibels at 3 metres
Battery Life:	1 year minimum
Detection Method:	Photoelectric sensor
Low battery indication:	Chirps when battery needs replacing
Alarm duration:	As long as smoke is present, resets when smoke clears.
Mute mode:	When in Mute mode, the unit is desensitized for 10 minutes.
Mute indication:	Red LED flash every 30 seconds for 10 minutes, then resets.
Tested & Passed to:	AS3786-1993
Dimension:	103mm diameter x 40mm high.



Both models have same feature except the LIFPE9M has Mute feature.



FIRE • SECURITY • INTERCOMS

psaproducts.com.au

1300 772 776

enquiry@psaproducts.com.au