

125-150 A

DS9

DECONTACTOR™ SWITCH + SOCKET-OUTLET



**IK09 METAL version
available**



150 A



IP66/IP67
IP69



GRP



IK08



-40°C
+60°C



AC-22
AC-23



Voltages

**Pole
configuration**

**Panel
mounted
Socket**

**Inclined
socket**

**Wall
mounting
socket**

**Coupler
socket**

Plug

**Appliance
inlet**

380-440 V AC	3P+E + accessories	3194013 /	3194013 515M3	3194013 595C3M40 ⁽¹⁾	3194013 555P0D35 ⁽²⁾	3198013 555P0D35 ⁽²⁾	3198013 /
220-250 V AC	3P+N+E + accessories	3194017 /	3194017 515M3	3194017 595C3M40 ⁽¹⁾	3194017 555P0D35 ⁽²⁾	3198017 555P0D35 ⁽²⁾	3198017 /
380-440 V AC							

(1) M40 threading - (2) Gland size 25-35 mm.

DX9

DECONTACTOR™ SWITCH + SOCKET-OUTLET



II 2 G D Ex de IIC T6/5 tD A21 T80°C/90 °C



125 A



IP65/IP66



METAL



IK10



-25°C
+60°C



AC-22



Voltages

**Pole
configuration**

Wall mounting socket

Coupler socket

Plug

380-440 V AC	3P+E + accessories	2694013 269AB5350M ⁽¹⁾	2694013 269A95350M ⁽¹⁾	2691013 ⁽²⁾ /
380-440 V AC	3P+N+E + accessories	2696017 269AB5350M ⁽¹⁾	2694017 269A95350M ⁽¹⁾	2691017 ⁽²⁾ /

(1) Gland size 23-35 mm - (2) Gland size 16-27 mm.

ACCESSORIES AND OPTIONS



**Locking pin for
2 padlocks 8 mm
(padlocks not supplied)**



Inlet cap IP55



Inlet cap IP65

DECONTACTOR™

DS9	Socket ref. + 844	319A126	/
DX9	Included	/	266A926