

# Building Wires -Twin + Earth, and 3 Cores + Earth

Easy-tear sheath for general wiring, unenclosed, closed in conduit buried direct or in underground ducts for domestic, commercial and industrial installations where not subject to mechanical damage.

Plain annealed copper (AS/NZS 1125)

PVC V90


3V-90 Easy-tear White

450/750 V

100m, 500m

75°C

Red, Black & Green/Yellow  
Red, Blue, White & Green/Yellow



## Typical Features

Electra Cables Part No.	Stranding No./mm	Insulation Thick mm	Sheath Thickness mm	Nom. O/D mm	Min. Installed Bending Radius mm		Approx. Mass Kg/Km	Order Now
					Minor	Major		
SRF3010V	2x1/1.13 + E 7/0.50E	0.6	0.9	9.0x4.3	20	40	90	
SRF3015V	2x7/0.50+7/0.50E	0.6	0.9	10x4.7	20	45	110	
SRF3025V	2x7/0.67+7/0.67E	0.7	1	12.4x5.6	25	50	165	
SRF3040V	2x7/0.85+7/0.67E	0.8	1.1	14.2x6.4	30	60	200	
SRF3060V	2x7/1.04+7/0.67E	0.8	1.1	15.3x7.1	30	70	285	
SRF3100V	2x7/1.35+7/0.85E	1	1.2	18.9x8.7	35	85	425	
SRF3160V	2x7/1.70+7/1.04E	1	1.3	21.8x9.9	40	95	610	
SRF4015V	3x7/0.50+7/0.50E	0.6	0.8	12.5x4.5	20	55	145	
SRF4025V	3x7/0.67+7/0.67E	0.7	1	15.9x5.6	25	70	190	