

## Product data sheet

### Characteristics

# 32ELEDM2-WE

Rotary LED Dimmer, 30 Series Module, 150W,  
240V AC, White Electric



### Main

Range	C2000 Series
Product or component type	Dimmer
Device presentation	Mechanism
Dimmer type	Trailing edge
Colour tint	White electric (WE)
Type of packing	Box
Load type	Dimmable LED - 150 W Incandescent - 150 W

### Complementary

Range compatibility	Clipsal
Fixing mode	Clip-in
Surface finish	Glossy
Ambient air temperature for storage	0...60 °C
Dimmer control	Rotary
[Ue] rated operational voltage	220...240 V AC 50 Hz 150 W
Function available	Brightness adjustment
Protection type	Short-circuit Overload protection Thermal protection
Ambient air temperature for operation	0...45 °C
Relative humidity	5...90 %
Connections - terminals	2-wire supply
Material	PC (UL94 V-2): top PC MAS056 (UL94 V-2): bottom
Height	22.84 mm
Width	22.84 mm
Depth	54.7 mm
Embedding depth	39 mm

### Environment

Standards	AS/NZS 60669.2.1
IP degree of protection	IP20

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.0 cm
Package 1 Width	7.8 cm
Package 1 Length	9.5 cm
Package 1 Weight	57.0 g
Unit Type of Package 2	PAL

Number of Units in Package 2	2304
Package 2 Height	105.0 cm
Package 2 Width	114.0 cm
Package 2 Length	114.0 cm
Package 2 Weight	192.0 kg
Unit Type of Package 3	CAR
Number of Units in Package 3	48
Package 3 Height	22.7 cm
Package 3 Width	26.4 cm
Package 3 Length	33.8 cm
Package 3 Weight	3.67 kg

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End Of Life Information</a>