

TPBHS1

Clipsal LED bulkhead - 20W - 1100 lm - 4000K -
IP54 - Grey body - Rectangle



Main

Range	Clipsal
Product name	TPBH Series
Product or component type	Bulkhead
Device application	Lighting

Complementary

Type of installation	Outdoor
Operational power in W	20 W
Light source	LED
[Ue] rated operational voltage	240 V AC 50 Hz
Colour rendering index	R _a =70
Luminous flux	1100 lm
Bulb lifespan	36000 h
Colour temperature	4000 K
Colour	Grey body
Device mounting	Surface DIN rail
Mounting mode	Surface mounted
Shape	Rectangular
Height	130 mm
Width	220 mm
Depth	36 mm
Product weight	0.536 kg
Targeted country	Australia

Environment

IP degree of protection	IP54
ambient air temperature for operation	-10...40 °C
relative humidity	10...95 % non-condensing

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.