



CLEVERTRONICS LP PREMIUM CLEVERFIT LED EXIT



PRODUCT INFORMATION

Catalogue Number	CCFLED
Description	LED LP Premium Cleverfit Exit, 24 metre viewing Distance
Construction	ABS Body with ABS Diffuser and Polycarbonate Clear tamper proof cover.
Mounting	Wall, Ceiling Single-Sided & Ceiling Double-Sided
Dimensions L x W x H	355mm x 80mm x 215mm
Operating Mode	Maintained
Testing System	Manual Test Switch
Charging Method	Intelligent current limited constant voltage charger
Diffuser	(All directional inserts included in the box)
Lamp(s)	6 x high intensity, low energy LED, surface mounted onto a replaceable lamp bar, 100,000 hour
Operating Voltage	240V 50Hz
Power Consumption	2.7W Standby (5.1W during first 16hr charge)
IP Rating	IP20
Operating Temperature	1° to 40°C
AS/NZS2293 Classification	C ₀ =E2.5 C ₉₀ =E2

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550190	Battery: LP 3.2 Volt 1.5Ah Li-ion
8002325	PCA: LP LED Cleverfit Driver, #CT10164-L4
8002120	PCA: DLED Cleverfit Light Strip, #CT10152-D2

