



### Main

Range of product	NSX100...250
Product or component type	Trip unit
Range compatibility	Compact NSX100 Compact NSX160 Compact NSX250
Device application	Motor
Poles description	3P
Protected poles description	3t
Network type	AC
Network frequency	50/60 Hz
Trip unit name	MA
Trip unit technology	Magnetic
Trip unit protection functions	I
Trip unit rating	
Protection type	Short-circuit protection (magnetic)

### Complementary

Mounting mode	Fixed
[Ue] rated operational voltage	690 V AC 50/60 Hz
Short-time pick-up adjustment type Isd	Adjustable 9 settings
[Isd] short-time pick-up adjustment range	6...14 x In

### Environment

standards	EN 60947-2 IEC 60947-2 NEMA AB1 UL 508
product certifications	CSA UL
IP degree of protection	IP40 conforming to IEC 60529
pollution degree	3 conforming to IEC 60947-1
ambient air temperature for operation	-25...70 °C
ambient air temperature for storage	-50...85 °C

### Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0819 - Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.