



3Ps125 Handle Suits Cable Diam 22-39Mm

- Available in five sizes including 30A, 50A, 90A, 150A and 250A (Maximum current rating to IEC60309-3)
- 3, 4 and 5 pin configurations with optional pilot pins, silver alloy tipped for low voltage drop and high arc resistance
- AC23 rating for making and breaking high inductive loads
- Connect and disconnect under load, eliminates the need for switching
- Interlocked socket and appliance inlet with 24 insert settings (Factory Set) preventing mismatching for a safe and reliable connection
- High ingress protection and exceptional impact resistance, IP66 / IK 08
- Resistance to most industrial chemicals, detergents and exposure to UV light
- Range of angled wall boxes, incline sleeves and handles for all plug and socket combinations

Representative Photo Only
(actual product may vary based on configuration selections)

SPECIFICATIONS

Component Type Plugs And Sockets	Accessory
Diameter, Cable Jacket, Min	22 mm
Diameter, Cable Jacket, Max	39 mm
Standards Compliance	AS/NZS 3947.3 IEC 60309-1 IEC 60529 IEC 60947-3

REFERENCES

IECEX Certificate	-
Supplier Declaration of Conformity:	-
Installation Guide:	-
User Manual:	-
Manufacturer Datasheet:	-
Manufacturer Catalogue & Product Selection:	-

Catalogue No: **3PS9G**

3PS125 HANDLE SUITS CABLE DIAM 22-39mm

Plugs, Sockets and Switches > Isolating Plugs and Sockets > Isolating Plugs and Sockets > Proconnect Plugs and Sockets > 150A Deconnector Plugs and Sockets (3PS125 Series) > Accessories

