



### Main

Product brand	Clipsal
Range of product	Series 4 Wilco

### Complementary

Curve code	C
Number of poles	1
[In] rated current	50 A
[Ue] rated operational voltage	240 V
Breaking capacity	4.5 kA conforming to EN 60898
Network type	AC
Limitation class	3
Network frequency	50/60 Hz
Number of modules	1
Depth	73 mm inner

### Environment

pollution degree	3
IP degree of protection	IP20 IP40
ambient air temperature for operation	-25...70 °C
standards	AS/NZS 60898

### Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0627 - Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.