



Representative Photo Only  
(actual product may vary based on configuration selections)

CSB flush mount loadcentre, 12way, transparent door

- Standard AS/NZS 3439-3
- Suit MOD6 MCBs, RCDs & RCBOs
- IP40 rating
- Split neutral and earth bars rated 100A
- Removable earth and neutral bar
- White or transparent door
- Door hinged at the top
- Supplied complete with busbar comb
- Base (ABS)
- Door (white -ABS), (transparent (polycarbonate))
- 8way- Neutral split 4/4 & 8way earth, 12way- Neutral split 5/3/3 & 12way earth
- 18way- Neutral split 9/3/3/3 & 18way earth, 24way- Neutral split 10/3/3/3/3 & 24way earth
- 36way- Neutral split 12/12/12 & 36way earth

**SPECIFICATIONS**

Component Type	Power Distribution & Protection	Loadcentre Enclosure
Item Description	CSB flush mount loadcentre, 12way, transparent door	
IP rating	IP40	
Number of Poles	12	
MCB Type	DIN Profile	
Material, body / housing	ABS (Acrylonitrile Butadiene Styrene)	
Colour, body / housing	White	
Colour, door	Clear / Transparent	
Ue, rated operational voltage, AC, 3ph, nom	415	
Ue, rated operational voltage, AC, 1ph, nom	240	
In, rated current	100	
In, rated current, busbar comb, centre feed	130	
In, rated current, busbar comb, end feed	80	
Tunnels, neutral bar	5/3/3	
Tunnels, earth bar	12	
Mounting	Flush Mount	
Height	200	
Width	256	
Depth	97	
zzzEarth and Neutral bar Rating	100A 16 mm tunnel terminals	
Standards Compliance	AS/NZS 3439.3	

# Catalogue No: **CSB12FT**

## LOADCENTRE 12 WAY DIN FLUSH TRANSPARENT DOOR

Power Distribution and Protection > Distribution Boards > Loadcentre Assemblies > MOD6 Range of Loadcentres > MOD6 CSB Loadcentres > Insulated Flush Mount Transparent Door



### REFERENCES

IECEX Certificate -

Supplier Declaration of  
Conformity: -

Installation Guide: -

User Manual: -

Manufacturer Datasheet: -

Manufacturer Catalogue  
& Product Selection: -